

The future of grilling is smart!



PG 8138 SEVO SMART CONTROL GT

USP at a glance:

- Smart grilling – with the smart app control, complex dishes turn out by themselves
- Simple control via the intuitive OLED display and always full control by the integrated core thermometer
- Low and slow - Thanks to the 3-zone heating technology and lid, no grill wishes remain unfulfilled
- BoostZone - 500 ° C for excellent brandings and perfect steaks



APP CONTROL



OLED DISPLAY &
2 THERMOMETERS



500 °C BOOST ZONE &
3-ZONE HEATING



PERFECT STEAK

Product details



Modular construction:

Many parts are removable, which makes cleaning easy



BoostZone

Full power thanks to the specially developed double heating



Grill rack

Split stainless steel grillage for best performance and easy cleaning (Ø7mm)



Water in the reflector cup

For easy cleaning, against grease fire and smoke formation. The bowl has a capacity of 2 liters.



SafeTouch

We are already stopping today the guidelines of tomorrow. Of course, the SEVO heats up - but not so hot that you burn yourself on it.



XXL power cord

2m long power cord makes it easier to choose a place and provides more flexibility.




3-zone heating

The specially developed heater has three modes:

LowZone - ideal for low & slow dishes and for cooking steaks

HotZone - ideal for grilling at temperatures up to 340 ° C

BoostZone - full power with up to 500 ° C for the perfect steak



Comprehensive app

Optionally, the SEVO SMART CONTROL can also be controlled via the SEVERIN app and checked at any time. Functions such as the timer and core thermometer can also be used conveniently here. Even complex dishes are guaranteed to succeed thanks to Grillmaster function.

Important data

Power in Watt	3.000 Watt
Colour	St/St-black
Grill area	Ca. 41,5 cm x 31,5 cm
LED-Ring	Standby: Blue LowZone: Violett HotZone: Orange BoostZone: Red
Grillthermometer	Yes, up to two temperature probes (10°C – 300°C)
Timer	Yes, up to 23h 59min
Grilltemperature	LowZone: 80°C – 200°C HotZone: 80°C – 340°C (320°C bei geschlossenem Deckel) BoostZone: 330°C – 500°C
Power Cord	2,00 m
Automatic shut off	Safety microswitch, heating element switches off automatically when removed
Product dimension (without stand)	57 cm x 32 cm x 50 cm
Product weight	18 kg
Dimensions incl. packaging	64,5 x 57 x 36,5 cm
Weight incl. packaging	18,6 kg
PU	1
GTIN-Code	4008146037443